LOC/DME I-SHR	APP CRS	Rwy Idg	8301
108.7	326°	TDZE	3985
Chan 24		Apt Elev	4021

ILS or LOC/DME RWY 33

SHERIDAN COUNTY (SHR)

T A -19°C — When local altimeter setting not received, procedure NA. Night landing: Rwy 24 NA. For inoperative MALSR, increase S-LOC 33 Cats C and D visibility to ⅞ mile.

MALSR

MISSED APPROACH: Climb to 7000 on heading 326° and on SHR VOR/DME R-127 to SHR VOR/DME and hold, continue climb-in-hold to 7000.

ASOS	SALT LAKE CENTER	UNICOM
135.175	127.75 351.9	123.0 (CTAF) L

SHERIDAN 113.55 SHR Chan 82(Y)

R-316 136° 316° R-127

9700 to KEKNE 143° (26.2)

LOCALIZER 108.7 I-SHR Chan 24

MSA SHR 25 NM: 113° 6700 308° 14400

4097 4674 4328 4022± 4753

CIVSA I-SHR 4.9

NITLE I-SHR 8.1

FEKLI I-SHR 11.5

SORKE I-SHR 15.3

5802 5607 7200 326° (3.8) 5726 (6.3)

(IF/IAF) KEKNE I-SHR 21.5

326° 7900 146° 1 min 326° 146° 318° (31.1)

9100 NoPT to KEKNE

IAF CRAZY WOMAN 117.3 CZI Chan 120

DME REQUIRED

9489 10147 10828 11050 9358 8680 11560 11760 13167 11112 6827

5000 7000 9000 11000

ELEV 4021 D TDZE 3985

5039 X 75 1.6% UP 4007

8301 X 100 0.4% UP 33

0.5% DOWN 15 9 24

HIRL Rwy 15-33 L

MIRL Rwy 6-24 L

REIL Rwys 6, 15, and 24 L

326°

7000 hdg 326° | SHR R-127 | SHR

Use I-SHR DME when on the localizer course.

*LOC only. *I-SHR I-SHR 2.3 I-SHR 1.5 CIVSA I-SHR 4.9 NITLE I-SHR 8.1 FEKLI I-SHR 11.5 SORKE I-SHR 15.3 KEKNE I-SHR 21.5 One Minute Holding Pattern

5100* 6100* 7200 7200 326° 7900 146° 326° 9100

GS 3.00° TCH 55

0.8 2.6 NM 3.2 NM 3.4 NM 3.8 NM 6.3 NM

CATEGORY	A	B	C	D
S-ILS 33	4185-½ 200 (200-½)			
S-LOC 33	4280-½ 295 (300-½)			
C CIRCLING	4600-1 579 (600-1)	4640-1 619 (700-1)	4860-2½ 839 (900-2½)	5220-3 1199 (1200-3)

NW-1, 15 MAY 2025 to 12 JUN 2025
NW-1, 15 MAY 2025 to 12 JUN 2025