

LOC/DME I-VAC <b>110.75</b> Chan 44 (Y)	APP CRS <b>006°</b>	Rwy Idg <b>8000</b>
		TDZE <b>873</b>
		Apt Elev <b>896</b>

# ILS or LOC RWY 36L


CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

**Simultaneous approach authorized with Rwy 36C and 36R. DME required.**


**ALSIF-2**

**MISSED APPROACH:** Climb to 3000 then climbing left turn to 3000 via heading 270° and CVG R-294 to JADRO/CVG 16 DME and hold.

D-ATIS ARR <b>134.375</b> DEP <b>135.3</b>	CINCINNATI APP CON <b>119.7 363.15</b> (090°-269°) <b>123.875 363.15</b> (270°-089°)	CINCINNATI TOWER <b>118.975 360.85</b> (RWY 18L/36R) <b>118.3</b> (RWYS 18C/36C, 09/27) <b>133.325</b> (RWY 18R/36L)	GND CON <b>121.7</b>	CLNC DEL <b>127.175</b>	CPDLC
---	--	---	-------------------------	----------------------------	-------



BRTCL I-VAC 14.2	1300	3000	CVG R-294	JADRO	ELEV 896	TDZE 873
Procedure Turn NA	RADAR BEPEE I-VAC 11.1	CUTAC RADAR I-VAC 7.9	ROPRR I-VAC 6	JIMUR I-VAC 3.1	**LOC only.	
GS 3.00° TCH 55	5000	4000	3000	006°	2400	2400
	3.1 NM	3.1 NM	1.9 NM	2.9 NM	0.7	0.2
CATEGORY	A	B	C	D		
S-ILS 36L	1073/18		200 (200-½)			
S-LOC 36L	1440/24	567 (600-½)	1440/60	567 (600-1¼)		
CIRCLING	1460-1	564 (600-1)	1560-1¾	664 (700-1¾)	1560-2	664 (700-2)
JIMUR FIX MINIMUMS						
S-LOC 36L	1220/24	347 (400-½)	1220/30	347 (400-¾)		
CIRCLING	1460-1	564 (600-1)	1560-1¾	664 (700-1¾)	1560-2	664 (700-2)



SE-1, 15 MAY 2025 to 12 JUN 2025

SE-1, 15 MAY 2025 to 12 JUN 2025