RNAV (GPS) RWY 17R

ORLANDO INTL (MCO)

WAAS	APP CRS	Rwy Idg	10000
CH 72913	185°	TDZE	90
W17A		Apt Elev	96

RNP APCH-GPS.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1° C or above 54° C. Bright lights on highway midway between Rwy 17L and Rwy 17R may be mistaken for runway lights. Simultaneous approach authorized with Rwy 17L and Rwy 18L, or Rwy 17L and Rwy 18R. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV Cats C/D visibility to 1⅝ SM.

ALSF-2

MISSED APPROACH: Climb to 3000 direct FOBUK and hold.

D-ATIS	ORLANDO APP CON	ORLANDO TOWER	GND CON	CLNC DEL	
ARR 121.25	124.8 307.0	118.45 253.5 (Rwys 17L-35R,17R-35L)	126.4 (East)	134.7	CPDLC
DEP 120.525		124.3 253.5 (Rwys 18L-36R,18R-36L)	121.8 (West)	341.7	

RADAR REQUIRED

(IAF) SACRO
4000
185° (6.3)
(IF) DALTY
3000
185° (3.2)
ELLAN
2500
185° (1.6)
GLOSI
Exec
1600
185° (2.8)
(FAF) MINCO
215
353
464
RW17R
214
346
549
1749
1749

MISSED APCH FIX
FOBUK
185°
5005
4 NM

MSA RW17R 25 NM
3000

ELEV 96 D TDZE 90

185°

18R 18L 17L 17R 12004 X 200 12005 X 200 10006 X 150 10000 X 150 TWR 437 ± 36L 36R 35R 35L

HIRL all Rwys
REIL Rwy 36L
TDZ/CL Rwys 17L/R,18R, 35L/R and 36R

VGSI and RNAV glidepath not concident (VGSI Angle 3.00/TCH 71).

3000 FOBUK

SACRO DALTY ELLAN GLOSI MINCO 1.6 NM to RW17R RW17R

4000 185° 4000 3000 2500 1600

GP 3.00° TCH 53

6.3 NM 3.2 NM 1.6 NM 2.8 NM 2.9 NM 1.6 NM

CATEGORY	A	B	C	D
LPV DA	290/18 200 (200-½)			
LNAV/VNAV DA	526/50 436 (500-1)			
LNAV MDA	660/24 570 (600-½)		660-1¼ 570 (600-1¼)	
C CIRCLING	740-1 644 (700-1)		740-1¾ 644 (700-1¾)	740-2 644 (700-2)

SE-3, 15 MAY 2025 to 12 JUN 2025
SE-3, 15 MAY 2025 to 12 JUN 2025