

SCOTTSBLUFF**WESTERN NEBRASKA RGNL/WILLIAM B HEILIG FLD** (BFF)(KBFF) 3 E UTC-7(-6DT) N41°52.44' **CHEYENNE**

W103°35.74'

H-5A, L-12F

3967 B ARFF Index—See Remarks NOTAM FILE BFF

IAP, AD

RWY 12-30: H8279X150 (ASPH) S-109, D-178, 2S-139, 2D-321

PCN 42 F/A/W/T HIRL

RWY 12: MALSR. PAPI(P4L)—GA 3.0° TCH 57'.**RWY 30:** MALSR. PAPI(P4L)—GA 3.0° TCH 53'.**RWY 05-23:** H8002X150 (ASPH) S-98, D-158, 2D-285

PCN 37 F/A/W/T MIRL

RWY 05: VASI(V4L)—GA 3.0° TCH 50'.**RWY 23:** PAPI(P4L)—GA 3.0° TCH 52'. Road.**RUNWAY DECLARED DISTANCE INFORMATION****RWY 05:** TORA-8002 TODA-8002 ASDA-8002 LDA-8002**RWY 12:** TORA-8279 TODA-8279 ASDA-8279 LDA-8279**RWY 23:** TORA-8002 TODA-8002 ASDA-8002 LDA-8002**RWY 30:** TORA-8279 TODA-8279 ASDA-8279 LDA-8279**SERVICE:** S4 FUEL 100LL, JET A OX2 LGT ACTIVATE MIRL Rwy

05-23, HIRL Rwy 12-30, MALSR Rwy 12 and Rwy 30, and VASI Rwy

05, PAPI Rwy 12, Rwy 23 and Rwy 30—CTAF.

AIRPORT REMARKS: Attended 1300-0400Z. For svc after hrs call

308-635-0162. Waterfowl on and in/ovf arpt. Rwy 30 designated calm

wind rwy. Line of site restrictions between apch ends of Rwy 05 and

Rwy 30 and also between the apch ends of Rwy 12 and Rwy 23. Apron pavement strength, S-85, D-117, DT-232. PCN

is 31 R/A/W/T. Class I, ARFF Index A. PPR 24 hrs for air carrier ops with more than 30 passenger seats call arpt manager

308-635-4941. Air carrier ops over 9 passenger seats not authorized in excess of 15 minutes before or after scheduled

arrival/departure times except with prior coordination with arpt manager. ARFF index B equipment is provided. Per arpt

manager use CTAF when operating on the arpt. AC and DC ground power units available. Lavatory service available.

AIRPORT MANAGER: 308-635-4941**WEATHER DATA SOURCES:** ASOS 121.025 (308) 632-8949.**COMMUNICATIONS:** CTAF/UNICOM 123.0**SCOTTSBLUFF RCO** 122.6 (COLUMBUS RADIO)**RCO** 122.1R 112.6T (COLUMBUS RADIO)® **DENVER CENTER APP/DEP CON** 127.95**AIRSPACE:** CLASS E**RADIO AIDS TO NAVIGATION:** NOTAM FILE BFF.**SCOTTSBLUFF (H) VORTAC** 112.6 BFF Chan 73 N41°53.65' W103°28.92' 244° 5.2 NM to fld. 4169/13E.

TACAN AZIMUTH & DME unusable:

025°-060° 25 NM blo 6,300'

310°-025° 25 NM blo 6,500'

CREVE NDB (LOMW) 263 BF N41°48.15' W103°29.93' 305° 6.1 NM to fld. 3821/10E.**ILS/DME** 110.35 I-RMT Chan 40(Y) Rwy 12. Class IB. LOC unusable wi 0.3 NM to thld.**ILS/DME** 109.3 I-BFF Chan 30 Rwy 30. Class IB. LOM CREVE NDB. OM unmonitored. LOC unusable 0.3 NM to thld; byd 16° left of course; byd 25° right of course.