

LOC I-PYU 110.35	APP CRS 003°	Rwy Idg 5999
		TDZE 650
		Apt Elev 654

LOC RWY 36

ILLINOIS VALLEY RGNL-WALTER A. DUNCAN FIELD (VYS)


NA When local altimeter setting not received, use Marshall County altimeter setting and increase all MDA 80 feet; increase S-36 Cats C and D visibility 1 1/2 miles, increase Circling Cat C visibility to 2 miles and Circling Cat D visibility to 3 miles. WITAT fix minimums: increase S-36 Cats C and D visibility to 1 1/2 miles, increase Circling Cat C visibility to 2 miles and Cat D visibility to 3 miles. Inop table does not apply to Cats A and B. For inop ODALS, increase Cats C and D visibility to 1 1/2 miles. WITAT fix minimums: Inop table does not apply. For inop ODALS when using Marshall County altimeter setting, inop table does not apply to Cats A and B. For inop ODALS, increase Cats C and D visibility to 1 1/2 miles. WITAT fix minimums: inop table does not apply to Cats A and B, increase Cats C and D visibility to 1 1/2 miles.

ODALS
MISSED APPROACH: Climb to 1100 then climbing right turn to 3000 on heading 063° and on BDF VORTAC R-058 to KELSI INT/BDF 31.8 DME and hold.



AWOS-3
120.025

CHICAGO CENTER
123.75 259.1

UNICOM
123.0 (CTAF)



ELEV 654	TDZE 650
678±	



CATEGORY	A	B	C	D
S-36	1140-1	490 (500-1)	1140-1 1/4	490 (500-1 1/4)
CIRCLING	1140-1	1240-1	1260-1 3/4	1460-2 1/2
	486 (500-1)	586 (600-1)	606 (700-1 3/4)	806 (900-2 1/2)
WITAT FIX MINIMUMS				
S-36	1000-1 350 (400-1)			
CIRCLING	1120-1	1240-1	1260-1 3/4	1460-2 1/2
	466 (500-1)	586 (600-1)	606 (700-1 3/4)	806 (900-2 1/2)

FAF to MAP 5.1 NM					
Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

EC-3, 12 OCT 2017 to 09 NOV 2017

EC-3, 12 OCT 2017 to 09 NOV 2017