




WAAS CH 40007 W20A	APP CRS 197°	Rwy Ldg 6948 TDZE -1 Apt Elev 4
--	------------------------	---

RNAV (GPS) Y RWY 20

LOUIS ARMSTRONG NEW ORLEANS INTL (MSY)

RNP APCH - GPS.		MALS 	MISSED APPROACH: Climb to 2000 direct POLY and on track 109° to SAFES and hold.
<p>▼ Rwy 20 helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to 1$\frac{3}{8}$ SM.</p>			

D-ATIS 127.55	NEW ORLEANS APP CON WEST 125.5 350.35 EAST 133.15 290.3	NEW ORLEANS TOWER 119.5 254.3	GND CON 121.9 273.525	CLNC DEL 120.925	CPDLC
-------------------------	---	---	---------------------------------	----------------------------	-------



CATEGORY	A	B	C	D
LPV DA		249/40	250 (300- $\frac{3}{4}$)	
LNAV/VNAV DA		325/40	326 (400- $\frac{3}{4}$)	
LNAV MDA	460/40	461 (500- $\frac{3}{4}$)	460/55	461 (500-1)
C CIRCLING	520-1	516 (600-1)	580-1 $\frac{1}{2}$ 576 (600-1 $\frac{1}{2}$)	600-2 596 (600-2)

SC-4, 07 AUG 2025 to 04 SEP 2025

SC-4, 07 AUG 2025 to 04 SEP 2025