TOP ALTITUDE:
5000
D-ATIS
127.75
CLNC DEL
125.2
CPDLC
GND CON
121.0 379.2 (Rwy 9-27)
121.9 379.2 (Rwys 18C-36C, 18L-36R)
121.65 379.2 (Rwy 18R-36L)
MEMPHIS TOWER
118.3 257.8 (Rwy 9-27)
119.7 257.8 (Rwys 18C-36C, 18L-36R)
128.425 257.8 (Rwy 18R-36L)
MEMPHIS DEP CON
124.15 385.45
N
NUYID
059° (2)
GENEH
BASAC
5000
SLONN
HENIR
RIBZZ
WRRTZ
090° (24)
023° (30)
190° (5)
094° (5)
273°
093°
360°
011°
012°
015°
180°
163°
161°
153°
860
TAKEOFF MINIMUMS:
Rwys 9, 18L/C/R, 27, 36L/C/R:
Standard with minimum climb of
500' per NM to 860.
NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.
NOTE: Turbojets only.
NOTE: Takeoff Rwys 18L/C/R, 36L/C/R-
RADAR required for non-GPS equipped aircraft.
NOTE: Takeoff Rwy 9, 27- RADAR required.
NOTE: Transponder code will be issued via
PDC or Memphis clearance delivery.
NOTE: Procedure authorized 0200-0600 local only.
NOTE: Accelerate to 250K, if unable advise ATC.
NOTE: If unable to accept climb rates, advise ATC on
initial contact.
(NARRATIVE ON FOLLOWING PAGE)
NOTE: Chart not to scale.