

LOC/DME I-PLJ 111.35 Chan 50 (Y)	APP CRS 273°	Rwy Idg TDZE Apt Elev	8002 8 8
--	------------------------	-----------------------------	-------------------------------------

ILS or LOC RWY 27R
MIAMI-OPA LOCKA EXECUTIVE (OPF)

▼ DME Required.
▲ When local altimeter setting not received, use Miami Intl altimeter setting and increase all DA/MDA 20 feet.
For inop MALS, increase S-ILS 27R all Cats visibility to ¾ mile and S-LOC Cats C/D visibility to 1½ mile.
Helicopter visibility reduction below ¾ SM NA.

MALS





MISSED APPROACH: Climb to 2000 heading 273° and DHP VORTAC R-335 to BRBRA/DHP 11.5 DME and hold.


ATIS 125.9	MIAMI APP CON 128.6 306.975	OPA LOCKA TOWER ★ 134.675 (CTAF) 0	GND CON 120.025	CLNC DEL 119.2
----------------------	---------------------------------------	--	---------------------------	--------------------------

RADAR REQUIRED

ALTERNATE MISSED APCH FIX



ELEV 8	D	TDZE 8
---------------	----------	---------------



MIRL Rwy 9R-27L
HIRL Rwys 9L-27R and 12-30

FAF to MAP 4.8 NM

Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

CATEGORY	A	B	C	D
S-ILS 27R	291-¾ 283 (300-¾)			
S-LOC 27R	420-¾	412 (500-¾)	420-1	412 (500-1)
CIRCLING	540-1	532 (600-1)	540-1½	560-2
			532 (600-1½)	552 (600-2)

SE-3: 19 JUL 2018 to 16 AUG 2018

SE-3: 19 JUL 2018 to 16 AUG 2018