



TAKEOFF MINIMUMS

- Rwy 7L: Standard with minimum climb of 565' per NM to 2800, or 1000-3 with minimum climb of 370' per NM to 2800, or 1500-3 for climb in visual conditions.
- Rwy 7R: 500-1¼ with minimum climb of 488' per NM to 2800, or 1500-3 for climb in visual conditions.
- Rwy 25R: Standard with minimum climb of 487' per NM to 2800, or 1500-3 for climb in visual conditions.
- Rwy 25L: Standard with minimum climb of 451' per NM to 2800, or 1500-3 for climb in visual conditions.

TAKEOFF OBSTACLE NOTES

- Rwy 7L: Multiple poles and vegetation beginning 912' from DER, 125' left of centerline, up to 30' AGL/2423' MSL. Cactus 3824' from DER, 96' right of centerline, 16' AGL/1596' MSL. Windsock 340' from DER, 354' right of centerline, 9' AGL/1488' MSL.
- Rwy 7R: Multiple antennas and vegetation beginning 546' from DER, 267' left of centerline, up to 52' AGL/1952' MSL. Multiple antennas and vegetation beginning 978' from DER, 431' right of centerline, up to 40' AGL/1609' MSL.
- Rwy 25R: Multiple antennas beginning 1.4 NM from DER, 1847' right of centerline, up to 96' AGL/1806' MSL.
- Rwy 25L: Pole 1127' from DER, 498' right of centerline, 36' AGL/1475' MSL. Pole 1184' from DER, 495' left of centerline, 32' AGL/1471' MSL.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 7L/R: Climbing left turn via PXR VORTAC R-336 northwestbound to 4000. Thence. . . Or, climb in visual conditions to cross Phoenix Deer Valley Airport at or above 2800, then via PXR VORTAC R-336 northwestbound to 4000. Thence. . .

TAKEOFF RUNWAYS 25L/R: Climbing right turn via heading 060° and PXR VORTAC R-336 northwestbound to 4000. Thence. . . Or, climb in visual conditions to cross Phoenix Deer Valley Airport at or above 2800, then via PXR VORTAC R-336 northwestbound to 4000. Thence. . .

. . . climbing left turn direct PXR VORTAC.