


**RADAR INSTRUMENT APPROACH MINIMUMS**

**FALLON NAS (KNFL),** (VAN VOORHIS FIELD), NV (Amdt 1, 15008 USN)

**ELEV 3935**

**RADAR<sup>1</sup> - (E) 120.85x 121.875x 257.65x 277.4x 308.4x 346.4x 360.2x** 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATh/</u> <u>HAA</u>	<u>CEIL-VIS</u>	
PAR	31L	3.5°/56/906	ABCDE	<b>4126-¾</b>	200	(200-¾)	
	31R	3.5°/53/872	ABCDE	<b>4126-¾</b>	200	(200-¾)	
	13L	3.0°/47/885	ABCDE	<b>4134-¾</b>	200	(200-¾)	
	13R	3.0°/47/915	ABCDE	<b>4135-¾</b>	200	(200-¾)	
	7	3.0°/35/672	ABCDE	<b>4129-¾</b>	200	(200-¾)	
ASR	31L		ABCDE	<b>4220-1</b>	294	(300-1)	
	31R		ABCDE	<b>4220-1</b>	294	(300-1)	
	13R			AB	<b>4340-1</b>	405	(500-1)
				CDE	<b>4340-1½</b>	405	(500-1½)
	13L			AB	<b>4320-1</b>	386	(400-1)
				CDE	<b>4320-1½</b>	386	(400-1½)
	7			AB	<b>4340-1</b>	411	(500-1)
			CDE	<b>4340-1½</b>	411	(500-1½)	
CIR	ALL RWY		AB	<b>4400-1</b>	465	(500-1)	
			C	<b>4400-1½</b>	465	(500-1½)	
			D	<b>4520-2</b>	585	(600-2)	
			E	<b>4960-3</b>	1025	(1100-3)	

CAUTION: ATC Missed Approach Minimum Climb Rate to 7400

PAR/ASR	Rwy	Knots	60	120	180	240	300	360
	7	FPM	260	520	780	1040	1300	1560
	13L/R	FPM	260	520	780	1040	1300	1560
	31L/R	FPM	270	540	810	1080	1350	1620

<sup>1</sup>No-NOTAM MP sked: PAR-2200-0000Z++ Thu, ASR-1500-1700Z++ Wed, when ceil-vis 3000-5 and above.

11 OCT 2018 to 08 NOV 2018

11 OCT 2018 to 08 NOV 2018

**RADAR INSTRUMENT APPROACH MINIMUMS**

# RADAR MINS

18284

N2

## RADAR INSTRUMENT APPROACH MINIMUMS

**FORT HUACHUCA SIERRA VISTA, AZ**    Orig-A, 08NOV18 (18284) (FAA)    ELEV **4719**

**SIERRA VISTA MUNI-LIBBY AAF (FHU)**

RADAR-1 127.05 254.35 **▽ ▲** NA

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
PAR	26	3.00°/50/950	ABCDE	<b>4799</b> -¾	200	(100-¾)
	8	3.00°/41/782	ABCDE	<b>4919</b> -¾	200	(200-¾)
PAR W/O GS	8		AB	<b>5100</b> -1	381	(400-1)
			CDE	<b>5100</b> -1½	381	(400-1½)
	26		AB	<b>5080</b> -1	481	(400-1)
			CDE	<b>5080</b> -1½	481	(400-1½)
CIRCLING	ALL RWY		A	<b>5080</b> -1	381	(400-1)
			B	<b>5180</b> -1	461	(500-1)
			C	<b>5180</b> -1½	461	(500-1½)
			D	<b>5280</b> -2	561	(600-2)
			E	<b>5340</b> -2½	621	(700-2½)

Circling NA south of Rwy 8-30.

Procedure NA when control tower is closed.

**FORT HUACHUCA SIERRA VISTA, AZ**    Orig-A, 28JUN12 (14149) (FAA)    ELEV **4719**

**SIERRA VISTA MUNI-LIBBY AAF (FHU)**

RADAR-2 127.05 254.35 **▽ ▲** NA

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
ASR	26		AB	<b>5180</b> -1	581	(500-1)
			CDE	<b>5180</b> -1¾	581	(500-1¾)
			8	AB	<b>5380</b> -1	661
CIRCLING	26		CDE	<b>5380</b> -1½	661	(700-1½)
			AB	<b>5180</b> -1	461	(500-1)
			C	<b>5180</b> -1¾	461	(500-1¾)
			D	<b>5280</b> -2	561	(600-2)
			E	<b>5340</b> -2½	621	(700-2½)
	8		AB	<b>5380</b> -1	661	(700-1)
			C	<b>5380</b> -1½	661	(700-1½)
			D	<b>5380</b> -2	661	(700-2)
			E	<b>5380</b> -2½	661	(700-2½)

Circling NA south of Rwy 8-30.

ASR NA when tower is closed.

Circling Rwy 12-21 NA at night.

11 OCT 2018 to 08 NOV 2018

11 OCT 2018 to 08 NOV 2018

## RADAR INSTRUMENT APPROACH MINIMUMS

# RADAR MINS

18284

N2

SW-4

# RADAR MINS

18284

N3

## RADAR INSTRUMENT APPROACH MINIMUMS

### YUMA MCAS/YUMA INTL (KNYL), AZ (18144 USN)

ELEV 213

RADAR - (E) 120.9x 124.15x 125.55x 125.95x 254.0x 270.8x 278.7x 286.0x 301.2x 305.2x



	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	21R <sup>1</sup>	3.0°/54/1073	ABCDE	393-½	200	(200-½)
	3L	3.0°/54/1021	ABCDE	395-¾	200	(200-¾)
PAR W/O GS	3L		ABCDE	560-1	365	(400-1)
PAR W/O GS	21R <sup>2</sup>		AB	600-½	407	(400-½)
ASR			CDE	600-¾	407	(400-¾)
	3L		ABCDE	560-1	365	(400-1)
	3R		AB	600-1	412	(400-1)
			CDE	600-1⅙	412	(400-1⅙)
	21L		AB	600-1	392	(400-1)
			CDE	600-1⅙	392	(400-1⅙)
	21R <sup>3</sup>		AB	620-½	427	(500-½)
			CDE	620-¾	427	(500-¾)
CIRCLING	ALL RWY		A	680-1	467	(500-1)
			B	700-1	487	(500-1)
			C	800-1½	587	(600-1½)
			DE	800-2	587	(600-2)

<sup>1</sup>When ALS inop, increase CAT ABCDE vis to ¾ mile.

<sup>2</sup>When ALS inop, increase CAT ABCDE vis to 1¼ miles.

<sup>3</sup>When ALS inop, increase CAT AB vis to 1 mile, CAT CDE to 1¼ miles

11 OCT 2018 to 08 NOV 2018

11 OCT 2018 to 08 NOV 2018

SW-4

## RADAR INSTRUMENT APPROACH MINIMUMS

# RADAR MINS

18284

N3