

RADAR MINS


16315

N1

RADAR INSTRUMENT APPROACH MINIMUMS

FALLON NAS (KNFL), (VAN VOORHIS FIELD), NV (Amdt 1, 15008 USN)

ELEV 3935

RADAR¹ - (E) 120.85x 121.875x 257.65x 277.4x 308.4x 346.4x 360.2x 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATh/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	31L	3.5°/56/906	ABCDE	4126-¾	200	(200-¾)
	31R	3.5°/53/872	ABCDE	4126-¾	200	(200-¾)
	13L	3.0°/47/885	ABCDE	4134-¾	200	(200-¾)
	13R	3.0°/47/915	ABCDE	4135-¾	200	(200-¾)
	7	3.0°/35/672	ABCDE	4129-¾	200	(200-¾)
ASR	31L		ABCDE	4220-1	294	(300-1)
	31R		ABCDE	4220-1	294	(300-1)
	13R		AB	4340-1	405	(500-1)
			CDE	4340-1½	405	(500-1½)
	13L		AB	4320-1	386	(400-1)
			CDE	4320-1½	386	(400-1½)
7		AB	4340-1	411	(500-1)	
		CDE	4340-1½	411	(500-1½)	
CIR	ALL RWY		AB	4400-1	465	(500-1)
			C	4400-1½	465	(500-1½)
			D	4520-2	585	(600-2)
			E	4960-3	1025	(1100-3)

CAUTION: ATC Missed Approach Minimum Climb Rate to 7400

PAR/ASR	Rwy	Knots	60	120	180	240	300	360
	7	FPM	260	520	780	1040	1300	1560
	13L/R	FPM	260	520	780	1040	1300	1560
	31L/R	FPM	270	540	810	1080	1350	1620

¹No-NOTAM MP sked: PAR-2200-0000Z++ Thu, ASR-1500-1700Z++ Wed, when ceil-vis 3000-5 and above.

01 MAR 2018 to 29 MAR 2018

01 MAR 2018 to 29 MAR 2018

SW-4

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

16315

N1

RADAR MINS

16315

N2

RADAR INSTRUMENT APPROACH MINIMUMS

FORT HUACHUCA SIERRA VISTA, AZ Orig, 03MAY12 (14149) (FAA)

ELEV 4719

SIERRA VISTA MUNI-LIBBY AAF (FHU)

RADAR-1 127.05 254.35 **▽** **△** NA

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
PAR	26	3.00°/50/950	ABCDE	4799-¾	200	(100-¾)
	8	3.00°/41/782	ABCDE	4919-¾	200	(200-¾)
PAR W/O GS	8		AB	5100-1	381	(400-1)
			CDE	5100-1½	381	(400-1½)
	26		AB	5080-1	481	(400-1)
			CDE	5080-1½	481	(400-1½)
CIRCLING	ALL RWY		A	5080-1	381	(400-1)
			B	5180-1	461	(500-1)
			C	5180-1½	461	(500-1½)
			D	5280-2	561	(600-2)
			E	5340-2½	621	(700-2½)

Circling NA south of Rwy 8-30.

Procedure NA when control tower is closed.

Circling Rwy 12-21 NA at night.

FORT HUACHUCA SIERRA VISTA, AZ Orig-A, 28JUN12 (14149) (FAA)

ELEV 4719

SIERRA VISTA MUNI-LIBBY AAF (FHU)

RADAR-2 127.05 254.35 **▽** **△** NA

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
ASR	26		AB	5180-1	581	(500-1)
			CDE	5180-1¾	581	(500-1¾)
	8		AB	5380-1	661	(700-1)
			CDE	5380-1½	661	(700-1½)
CIRCLING	26		AB	5180-1	461	(500-1)
			C	5180-1¾	461	(500-1¾)
			D	5280-2	561	(600-2)
			E	5340-2½	621	(700-2½)
			8	AB	5380-1	661
	C	5380-1½	661	(700-1½)		
	D	5380-2	661	(700-2)		
	E	5380-2½	661	(700-2½)		

Circling NA south of Rwy 8-30.

ASR NA when tower is closed.

Circling Rwy 12-21 NA at night.

01 MAR 2018 to 29 MAR 2018

01 MAR 2018 to 29 MAR 2018

SW-4

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

16315

N2

RADAR MINS

16315

N3

RADAR INSTRUMENT APPROACH MINIMUMS

YUMA MCAS/YUMA INTL (KNYL), AZ (13234 USN)

ELEV 213

RADAR - (E) 120.9x 124.15x 125.55x 125.95x 254.0x 270.8x 278.7x 286.0x 301.2x 305.2x



	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u>		<u>CEIL-VIS</u>
				<u>MDA-VIS</u>	<u>HAA</u>	
PAR	21R ¹	3.0°/54/1062	ABCDE	393-½	200	(200-½)
	3L	3.0°/55/1014	ABCDE	392-¾	200	(200-¾)
PAR W/O GS	3L		ABCDE	560-1	368	(400-1)
PAR W/O GS	21R ²		ABCDE	620-¾	427	(500-¾)
ASR	3L		ABCDE	560-1	368	(400-1)
	3R		AB	600-1	412	(400-1)
			CDE	600-1½	412	(400-1½)
	21L		AB	620-1	413	(500-1)
			CDE	620-1½	413	(500-1½)
	21R ³		AB	620-½	427	(500-½)
			CDE	620-¾	427	(500-¾)
CIRCLING ⁴	ALL RWY		AB	680-1	467	(500-1)
			C	800-1½	587	(600-1½)
			DE	800-2	587	(600-2)

¹When ALS inop, increase CAT ABCDE vis to ¾ mile.

²When ALS inop, increase CAT ABCDE vis to 1¼ miles.

³When ALS inop, increase CAT AB vis to 1 mile, CAT CDE to 1¼ miles

⁴When circling from PAR W/O GS Rwy 21R, increase CAT ABC vis to 1¾ miles, CAT DE to 2¼ miles.

01 MAR 2018 to 29 MAR 2018

01 MAR 2018 to 29 MAR 2018

SW-4

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

16315

N3