


RADAR INSTRUMENT APPROACH MINIMUMS

FALLON NAS (KNFL), (VAN VOORHIS FIELD), NV (Amdt 1, 15008 USN)

ELEV 3935

RADAR¹ - (E) 120.85x 121.875x 257.65x 277.4x 308.4x 346.4x 360.2x 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	31L	3.5°/56/906	ABCDE	4126-¾	200	(200-¾)
	31R	3.5°/53/872	ABCDE	4126-¾	200	(200-¾)
	13L	3.0°/47/885	ABCDE	4134-¾	200	(200-¾)
	13R	3.0°/47/915	ABCDE	4135-¾	200	(200-¾)
	7	3.0°/35/672	ABCDE	4129-¾	200	(200-¾)
ASR	31L		ABCDE	4220-1	294	(300-1)
	31R		ABCDE	4220-1	294	(300-1)
	13R		AB	4340-1	405	(500-1)
			CDE	4340-1½	405	(500-1½)
	13L		AB	4320-1	386	(400-1)
			CDE	4320-1½	386	(400-1½)
	7		AB	4340-1	411	(500-1)
		CDE	4340-1½	411	(500-1½)	
CIR	ALL RWY		AB	4400-1	465	(500-1)
			C	4400-1½	465	(500-1½)
			D	4520-2	585	(600-2)
			E	4960-3	1025	(1100-3)

CAUTION: ATC Missed Approach Minimum Climb Rate to 7400

PAR/ASR	Rwy	Knots	60	120	180	240	300	360
	7	FPM	260	520	780	1040	1300	1560
	13L/R	FPM	260	520	780	1040	1300	1560
	31L/R	FPM	270	540	810	1080	1350	1620

¹No-NOTAM MP sked: PAR-2200-0000Z++ Thu, ASR-1500-1700Z++ Wed, when ceil-vis 3000-5 and above.

24 MAY 2018 to 21 JUN 2018

24 MAY 2018 to 21 JUN 2018

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

18144

N2

RADAR INSTRUMENT APPROACH MINIMUMS

FORT HUACHUCA SIERRA VISTA, AZ Orig. 03MAY12 (14149) (FAA) ELEV 4719

SIERRA VISTA MUNI-LIBBY AAF (FHU)

RADAR-1 127.05 254.35 NA

PAR	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HATH/	
PAR	26	3.00°/50/950	ABCDE	4799-¾	200	(100-¾)
	8	3.00°/41/782	ABCDE	4919-¾	200	(200-¾)
PAR W/O GS	8		AB	5100-1	381	(400-1)
			CDE	5100-1½	381	(400-1½)
	26		AB	5080-1	481	(400-1)
			CDE	5080-1½	481	(400-1½)
CIRCLING	ALL RWY		A	5080-1	381	(400-1)
			B	5180-1	461	(500-1)
			C	5180-1½	461	(500-1½)
			D	5280-2	561	(600-2)
			E	5340-2½	621	(700-2½)

Circling NA south of Rwy 8-30.
 Procedure NA when control tower is closed.
 Circling Rwy 12-21 NA at night.

FORT HUACHUCA SIERRA VISTA, AZ Orig-A, 28JUN12 (14149) (FAA) ELEV 4719

SIERRA VISTA MUNI-LIBBY AAF (FHU)

RADAR-2 127.05 254.35 NA

ASR	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HATH/	
ASR	26		AB	5180-1	581	(500-1)
			CDE	5180-1¾	581	(500-1¾)
	8		AB	5380-1	661	(700-1)
			CDE	5380-1½	661	(700-1½)
CIRCLING	26		AB	5180-1	461	(500-1)
			C	5180-1¾	461	(500-1¾)
			D	5280-2	561	(600-2)
			E	5340-2½	621	(700-2½)
			8	AB	5380-1	661
C	5380-1½	661		(700-1½)		
D	5380-2	661		(700-2)		
E	5380-2½	661		(700-2½)		

Circling NA south of Rwy 8-30.
 ASR NA when tower is closed.
 Circling Rwy 12-21 NA at night.

24 MAY 2018 to 21 JUN 2018

24 MAY 2018 to 21 JUN 2018

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

18144

N2

SW-4

RADAR MINS

18144

N3

RADAR INSTRUMENT APPROACH MINIMUMS

YUMA MCAS/YUMA INTL (KNYL), AZ (18144 USN)

ELEV 213

RADAR - (E) 120.9x 124.15x 125.55x 125.95x 254.0x 270.8x 278.7x 286.0x 301.2x 305.2x



	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
PAR	21R ¹	3.0°/54/1073	ABCDE	395-½	200	(200-½)
	3L	3.0°/54/1021	ABCDE	395-¾	200	(200-¾)
PAR W/O GS	3L		ABCDE	560-1	365	(400-1)
PAR W/O GS	21R ²		AB	600-½	407	(400-½)
ASR			CDE	600-¾	407	(400-¾)
	3L		ABCDE	560-1	365	(400-1)
	3R		AB	600-1	412	(400-1)
			CDE	600-1½	412	(400-1½)
	21L		AB	600-1	392	(400-1)
			CDE	600-1½	392	(400-1½)
	21R ³		AB	620-½	427	(500-½)
			CDE	620-¾	427	(500-¾)
CIRCLING	ALL RWY		A	680-1	467	(500-1)
			B	700-1	487	(500-1)
			C	800-1½	587	(600-1½)
			DE	800-2	587	(600-2)

¹When ALS inop, increase CAT ABCDE vis to ¾ mile.

²When ALS inop, increase CAT ABCDE vis to 1¼ miles.

³When ALS inop, increase CAT AB vis to 1 mile, CAT CDE to 1¼ miles

24 MAY 2018 to 21 JUN 2018

24 MAY 2018 to 21 JUN 2018

SW-4

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

18144

N3